Application Serial No.: 10/669,682

Reply to Office Action dated March 3, 2006

IN THE CLAIMS

Please amend the claims as follows:

- 1. (Currently Amended) A motion reduction apparatus for a floating body floating on water, said motion reduction apparatus comprising a plumb plate configured to be provided on at least a side of a floating main body, and configured to be separated from the floating main body by a specific distance, and configured to extend in a vertical orientation from beyond a lowermost bottom surface of the floating main body substantially in a vertical orientation.
- 2. (Currently Amended) A motion reduction apparatus according to claim 1, wherein the plumb plate is configured to be supported at a specific location of the floating main body by a plurality of stay members configured to be arranged on the floating main body in parallel so as to provide flow sections between that are surrounded by the floating main body, the plumb plate, and the stay members for flooding with incoming water.
- 3. (Previously Presented) A motion reduction apparatus according to claim 1, wherein the floating main body is orthorhombic-shaped, and the plumb plate is configured to be provided on at least a wavefront side section along a longitudinal direction of the floating main body.
- 4. (Currently Amended) A motion reduction apparatus according to claim 1, wherein the plumb plate is constructed so as to be vertically adjustable swing with respect to the floating main body.
 - 5.-11. (Canceled)
 - 12. (Previously Presented) A motion reduction apparatus for a floating body floating

Application Serial No.: 10/669,682

Reply to Office Action dated March 3, 2006

on water, said motion reduction apparatus comprising a plate member configured to be provided on a side of a floating main body disposed in such a way that an edge section of the plate member proximal to the floating main body is separated from the floating main body by a specific distance, wherein an upper edge of the plate member is configured to be oriented at substantially a same level as a lowermost bottom surface of the floating main body.

- 13. (Withdrawn) A motion reduction apparatus according to claim 12, wherein the plate member is disposed so as to be inclined at an angle with respect to a bottom surface of the floating main body.
- 14. (Currently Amended) A motion reduction apparatus according to claim 12, wherein the plate member is configured to be supported at a specific location of the floating main body by a plurality of stay members arranged in parallel on the floating main body so as to provide flow sections between that are surrounded by the floating main body, the plate member, and the stay members for flooding with incoming water.
- 15. (Previously Presented) A motion reduction apparatus according to claim 12, wherein the floating main body is orthorhombic-shaped, and the plate member is configured to be provided along a longitudinal direction at least on either a left side section or a right side section of the floating main body.
- 16. (Currently Amended) A motion reduction apparatus according to claim 12, wherein the plate member is constructed so as to be vertically adjustable swing with respect to the floating main body.
- 17. (Withdrawn) A motion reduction apparatus according to claim 12, wherein the plate member is supported vertically by hinging means.

Application Serial No.: 10/669,682

. 10/009,082

Reply to Office Action dated March 3, 2006

18. (Withdrawn) A motion reduction apparatus according to claim 17, wherein the plate member is supported on the hinging means arranged on the floating main body in parallel, and flow sections are provided in the hinging means for flooding with incoming water.

- 19. (Canceled)
- 20. (Canceled)
- 21. (Withdrawn) A motion reduction apparatus according to claim 1, wherein the plumb plate is subdivided by gaps formed substantially at right angles to a direction extending from the plumb plate.
 - 22. (Canceled)
- 23. (Withdrawn) A motion reduction apparatus according to claim 12, wherein the plate member is subdivided by gaps formed substantially at right angles to a direction extending from the plate member.
 - 24. (Canceled)
 - 25. (Canceled)
- 26. (Currently Amended) A floating body comprising a floating main body and a motion reduction apparatus according to any one of claims 1-4, 11 12-18, 21, or 23, 27 or 28.
- 27. (New) A motion reduction apparatus according to claim 1, wherein said plumb plate has a same longitudinal dimension as that of said floating main body.
- 28. (New) A motion reduction apparatus according to claim 12, wherein said plate member has a same longitudinal dimension as that of said floating main body.